

Cityline Core



Product Specification

| | |
|---------------|---------------------------------|
| Construction | Tufted High Low Loop |
| Pile Material | 100% Polyamid SD |
| Dye Method | 100% Solution Dyed |
| Backing | Unit Back® (PVC & Bitumen Free) |

| | Imperial | Metric |
|--------------|-----------------------|----------------------|
| Pile Height | 0.17 in | 4.5mm±0.5mm |
| Tile Size | 19.69 in X 19.69 | 50cm X 50cm |
| Stitch | 12 in | 47 / 10cm |
| Gauge | 1/12 in | 47.2 / 10cm |
| Pile Weight | 18 oz/yd ² | 610 g/m ² |
| Total Height | 0.24 in | 6±0.5mm |

Functional properties

| | | |
|---------------------|-----------|------------------------|
| Wear classification | 33-LC1 | |
| Hexapod tumbler | ISO 10361 | 12000 circle Grade≥3.5 |
| Use Density | Heavy | |

Physical properties

| | | |
|--------------------------------|----------------|-----------------|
| Impact sound insulation | ISO 10140 | ca. 23dB |
| Sound absorption | ISO 354 | $\alpha_w=0.25$ |
| Thermal resistance | ISO 8302 | ca. 0.07 |
| Burning classification | DIN EN 13501-1 | Cfl-s1 |
| Antistatic behavior | ISO 6356 | ≤2.0 kV |
| Light fastness | ISO 105 B02 | ≥6 |
| Water fastness | ISO 105 E01 | ≥4 |
| Resistance to abrasion dry-wet | ISO 105 X12 | ≥3-4 |
| Tuft bind | ISO 4919 | ≥30N |

Environmental Properties

| | |
|---------------|---------------------------|
| GUT | TVOC≤100µg/m ³ |
| Declare Label | |
| EPD | |


Warrant

15 Years Limited Wear Warranty
 Lifetime Anti-Static Limited Warranty
 Lifetime Anti-Fade Limited Warranty

Certifications



Installation



Monolithic