

Major Frequency: One Distortion

| SPECIFICATION | |
|----------------------------------|---|
| Construction | Tufted, Textured Loop |
| Face Fiber | 100% Milliken-Certified Nylon |
| Tile Size | 25cm x 100cm |
| Dye Method | Solution Dyed |
| Gauge | 1/12 |
| Stitches | 9.5 |
| Standard Backing | PVC-Free WellBAC™ Comfort Available with TractionBack® |
| Recyclability | 100% |
| Recycled Content By Total Weight | 18.9% (17.1% Post Industrial, 1.8% Post Consumer) |
| Nominal Total Thickness | 8.6mm |

| PERFORMANCE | WARRANTIES |
|---|-----------------------------------|
| Flammability (Radiant Panel ASTM-E-648) ≥ 0.45 (Class 1) | Lifetime Face Fiber Wear |
| Smoke Density (NFPA-258-T or ASTM-E-662) ≤ 450 | Lifetime Antistatic |
| Methamine Pill Test (CPSC FF-1-70 or ASTM D 2859) Self-Extinguishing | Lifetime Floor Compatibility |
| Lightfastness (AATCC 16E) ≥ 4.0 at 80 Hours | Lifetime Color Pattern Permanency |
| Crocking (AATCC 165) ≥ 4.0 Wet or Dry | Lifetime Floor Release |
| Static Electricity (AATCC-134) 20% R.H., 70° F. ≤ 3.5 KV, Permanent Conductive Fiber | Lifetime Moisture Resistance |
| Texture Appearance Retention Rating (TARR) Severe | Lifetime Delamination of Backing |
| Indoor Air Quality—CRI Green Label Plus™ GLP100130, Carpet Category 13X | Lifetime Dimensional Stability |
| | Lifetime Tuft Bind |
| | Lifetime Edge Ravel |
| | Lifetime Flammability |

INSTALLATION METHOD



Plank

3RD PARTY CERTIFICATES



Declare.

Design Copyright – Milliken & Company

This carpet tile product is covered by one or more patents, published applications and/ or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

Customer Service 8621 61455588 | millikencarpet.com