

# Compass

Ninety Degrees/Forty-Five Degrees/Zero Degrees

## SPECIFICATION

Construction	Tufted Loop
Face Fiber	100% Milliken-Certified Nylon
Tile Size	50 cm x 50 cm
Dye Method	Millitron®
Gauge	1/10
Stitches	14
Standard Backing	PVC-Free WellBAC® Comfort Available with TractionBack®
Recyclability	100%
Recycled Content By Total Weight	16.3% (14.4% Post Industrial, 1.9% Post Consumer)
Nominal Total Thickness	0.33" ( 8.5 mm)

## PERFORMANCE

Stain Resist / Soil Release	StainSmart®
Flammability (Radiant Panel ASTM-E-648)	≥ 0.45 (Class I)
Smoke Density (NFPA-258-T or ASTM-E-662)	≤ 450
Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859)	Self-Extinguishing
Lightfastness (AATCC 16E)	≥ 4.0 at 80 Hours
Crocking (AATCC 165)	≥ 4.0 Wet or Dry
Static Electricity (AATCC-134) 20% R.H., 70° F.	≤ 3.5 KV, Permanent Conductive Fiber
Texture Appearance Retention Rating (TARR)	Severe
Indoor Air Quality—CRI Green Label Plus™	GLP3237, Carpet Category 5Y

## WARRANTIES

Lifetime Face Fiber Wear
Lifetime Antistatic
Lifetime Floor Compatibility
Lifetime Color Pattern Permanency
Lifetime Floor Release
Lifetime Flammability
Lifetime Moisture Resistance
Lifetime Delamination of Backing
Lifetime Dimensional Stability
Lifetime Tuft Bind
Lifetime Edge Ravel
Lifetime Cushion Resiliency
Lifetime Staining/Soiling (StainSmart®)

## INSTALLATION METHOD



Monolithic

## 3<sup>RD</sup> PARTY CERTIFICATES



Declare.

Design Copyright – Milliken & Company . This carpet tile product is covered by one or more patents, published applications and / or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.