

DISSIDENT & FRINGE

Dissident / Fringe



SPECIFICATION

Construction	Tufted, Textured Loop
Face Fiber	100% Milliken-Certified Nylon
Tile Size	50 cm x 50cm
Dye Method	Millitron®
Gauge	1/12
Stitches	10.2
Standard Backing	PVC-Free WellBAC® Comfort Plus Available with TractionBack®
Recyclability	100%
Recycled Content By Total Weight	35.5% Post Industrial
Nominal Total Thickness	10.4 mm

PERFORMANCE

Stain Resist / Soil Release	StainSmart®
Flammability (Radiant Panel ASTM-E-648)	≥ 0.45 (Class I)
Smoke Density (NFPA-258-T or ASTM-E-662)	≤ 450
Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859)	Self-Extinguishing
Lightfastness (AATCC 16E)	≥ 4.0 at 80 Hours
Crocking (AATCC 165)	≥ 4.0 Wet or Dry
Static Electricity (AATCC-134) 20% R.H., 70° F.	≤ 3.5 KV, Permanent Conductive Fiber
Texture Appearance Retention Rating (TARR)	Severe
Indoor Air Quality—CRI Green Label Plus™	GLP3237, Carpet Category 5Y

WARRANTIES

- Lifetime Face Fiber Wear
- Lifetime Antistatic
- Lifetime Floor Compatibility
- Lifetime Color Pattern Permanency
- Lifetime Floor Release
- Lifetime Cushion Resiliency
- Lifetime Moisture Resistance
- Lifetime Delamination of Backing
- Lifetime Dimensional Stability
- Lifetime Tuft Bind
- Lifetime Edge Ravel
- Lifetime Flammability
- Lifetime Staining/Soiling (StainSmart®)

INSTALLATION METHOD



V-Ashlar Ashlar

3RD PARTY CERTIFICATES



Declare.

Design Copyright – Milliken & Company. This carpet tile product is covered by one or more patents, published applications and / or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.