

# Formwork 2.0

## Formwork



| SPECIFICATION                    |   |
|----------------------------------|---|
| Construction                     | Tufted, Textured Loop                                     |
| Face Fiber                       | 100% Milliken-Certified Nylon                             |
| Tile Size                        | 50cm x 50cm<br>25cmX100cm                                 |
| Dye Method                       | Solution Dyed   |
| Gauge                            | 1/10  |
| Stitches                         | 11.3  |
| Standard Backing                 | PVC-Free WellBAC® Comfort<br>Available with TractionBack® |
| Recyclability                    | 100%  |
| Recycled Content By Total Weight | 4.8% (2.4% Post Industrial, 2.4% Post Consumer)           |
| Nominal Total Thickness          | 5.8mm   |

| PERFORMANCE   |                                      | WARRANTIES                        |  |
|---|--------------------------------------|-----------------------------------|--|
| Flammability (Radiant Panel ASTM-E-648)             | ≥ 0.45 (Class I)                     | Lifetime Antistatic               |  |
| Smoke Density (NFPA-258-T or ASTM-E-662)            | ≤ 450                                | Lifetime Floor Compatibility      |  |
| Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859) | Self-Extinguishing                   | Lifetime Color Pattern Permanency |  |
| Lightfastness (AATCC 16E)                           | ≥ 4.0 at 80 Hours                    | Lifetime Floor Release            |  |
| Crocking (AATCC 165)                                | ≥ 4.0 Wet or Dry                     | Lifetime Face Fiber Wear          |  |
| Static Electricity (AATCC-134) 20% R.H., 70° F.     | ≤ 3.5 KV, Permanent Conductive Fiber | Lifetime Moisture Resistance      |  |
| Texture Appearance Retention Rating (TARR)          | Heavy                                | Lifetime Delamination of Backing  |  |
| Indoor Air Quality—CRI Green Label Plus™            | GLP3200, Carpet Category 14X         | Lifetime Dimensional Stability    |  |
|   |                                      | Lifetime Tuft Bind                |  |
|   |                                      | Lifetime Edge Ravel               |  |
|   |                                      | Lifetime Flammability             |  |

### INSTALLATION METHOD



Monolithic      Plank

### 3<sup>RD</sup> PARTY CERTIFICATES



Design Copyright – Milliken & Company.

This carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.