

Hues 2.0

Shades/Saturates

SPECIFICATION

Construction	Tufted, Textured Loop
Face Fiber	100% Milliken-Certified Nylon
Tile Size	50 cm x 50 cm
Dye Method	Solution Dyed
Gauge	1/12
Stitches	9.1
Standard Backing	PVC-Free WellBAC™ Function Available with TractionBack®
Recyclability	100%
Recycled Content By Total Weight	6.9% (4.4% Post Industrial, 2.5% Post Consumer)
Nominal Total Thickness	5.7mm

PERFORMANCE

WARRANTIES

Flammability (Radiant Panel ASTM-E-648)	≥ 0.45 (Class I)	Lifetime Antistatic
Smoke Density (NFPA-258-T or ASTM-E-662)	≤ 450	Lifetime Floor Compatibility
Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859)	Self-Extinguishing	Lifetime Color Pattern Permanency
Lightfastness (AATCC 16E)	≥ 4.0 at 80 Hours	Lifetime Floor Release
Crocking (AATCC 165)	≥ 4.0 Wet or Dry	Lifetime Face Fiber Wear
Static Electricity (AATCC-134) 20% R.H., 70° F.	≤ 3.5 KV, Permanent Conductive Fiber	Lifetime Moisture Resistance
Texture Appearance Retention Rating (TARR)	Heavy	Lifetime Delamination of Backing
Indoor Air Quality—CRI Green Label Plus™	GLP3200, Carpet Category 14X	Lifetime Dimensional Stability
		Lifetime Tuft Bind
		Lifetime Edge Ravel
		Lifetime Flammability

INSTALLATION METHOD



Monolithic

3RD PARTY CERTIFICATES



Declare.

Design Copyright – Milliken & Company.

This carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

Customer Service 8621 61455588 | millikencarpet.com
© 2020 Milliken & Company | Made in China