

Heavy Meta

Foundry/Alloy

SPECIFICATION

Construction	Tufted, Textured Loop
Face Fiber	ECONYL® Solution-Dyed Nylon
Tile Size	25 cm x 100 cm
Dye Method	Solution Dyed
Gauge	1/12
Stitches	7 for Foundry and 8.1 for Alloy
Standard Backing	PVC-Free WellBAC™ Comfort Available with TractionBack®
Recyclability	100%
Recycled Content By Total Weight	30% (20% Post Industrial, 10% Post Consumer)
Nominal Total Thickness	9.7mm


PERFORMANCE

Flammability (Radiant Panel ASTM-E-648)	≥ 0.45 (Class I)
Smoke Density (NFPA-258-T or ASTM-E-662)	≤ 450
Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859)	Self-Extinguishing
Lightfastness (AATCC 16E)	≥ 4.0 at 80 Hours
Crocking (AATCC 165)	≥ 4.0 Wet or Dry
Static Electricity (AATCC-134) 20% R.H., 70° F.	≤ 3.5 KV, Permanent Conductive Fiber
Texture Appearance Retention Rating (TARR)	Heavy
Indoor Air Quality—CRI Green Label Plus™	GLP100130, Carpet Category 13X

WARRANTIES

Lifetime Antistatic
Lifetime Floor Compatibility
Lifetime Color Pattern Permanency
Lifetime Floor Release
Lifetime Face Fiber Wear
Lifetime Moisture Resistance
Lifetime Delamination of Backing
Lifetime Dimensional Stability
Lifetime Tuft Bind
Lifetime Edge Ravel
Lifetime Flammability

INSTALLATION METHOD



Plank

3RD PARTY CERTIFICATES



Design Copyright – Milliken & Company.

This carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.