

Mixed Formations- Made of Stone

FlexForm™ LVT



SPECIFICATION

Construction	High Performance Flex Form LVT
Finish	ProGuard™ Reinforced Polyurethane Coating
Overall Thickness	5mm
Wear Layer Thickness	0.55mm
Edge Profile	Micro Bevel
Tile Sizes	18" x 36" / 457.2 x 914.4mm
Pieces Per Box	6
Weight Per Box	24.52kg
Quantity Per Box	2.51 m ²

PERFORMANCE

Critical Radiant Flux (ISO 9239-1)	≥4.5kW/m ²
Smoke Rate(ISO 9239-1)	<750%.min
Use Classification (ISO 10582)	Class 33 Heavy Commercial
Colour Fastness to Light (ISO 105-B02)	≥6
Slip Resistance (DIN 51130)	R10
Dimensional Stability (ISO 23999)	≤0.25 % ; Curl ≤2 mm
Resistance to Chemicals (ASTM F925)	Pass
Residual Indentation (ISO 24343-1)	≤0.1 mm
Castor Chair Resistance (ISO 4918)	Pass
Flexibility(ISO 24344)	Pass

WARRANTIES

15-Year Limited Commercial Wear

Installation

Glue Down

3RD PARTY CERTIFICATES





Milliken LVT is highly durable resilient flooring engineered with the highest quality raw materials to provide unsurpassed performance and enduring aesthetics. Milliken LVT is 100% ortho-phthalate-free. Milliken LVT is manufactured at facilities that are ISO 9001 and ISO 14001 compliant. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Images in this brochure are approximate for color and pattern scale. Please use actual product samples to make your final selections.