

## NATURE SUPPLY

Forest Rain/Forest Sound



## SPECIFICATION

Construction	Tufted, Textured Loop
Face Fiber	100% Milliken-Certified Nylon
Tile Size	25cm x 100cm (9.8" x 39.4")
Dye Method	Solution Dyed
Gauge	1/12
Stitches	9.1
Standard Backing	PVC-Free WellBAC™ Function Available with TractionBack®
Recyclability	100%
Recycled Content By Total Weight	6.9% (4.4% Post Industrial, 2.5% Post Consumer)
Nominal Total Thickness	0.21" ( 5.3mm)

## PERFORMANCE

Flammability (Radiant Panel ASTM-E-648)	≥ 0.45 (Class I)
Smoke Density (NFPA-258-T or ASTM-E-662)	≤ 450
Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859)	Self-Extinguishing
Lightfastness (AATCC 16E)	≥ 4.0 at 80 Hours
Crocking (AATCC 165)	≥ 4.0 Wet or Dry
Static Electricity (AATCC-134) 20% R.H., 70° F.	≤ 3.5 KV, Permanent Conductive Fiber
Texture Appearance Retention Rating (TARR)	Heavy
Indoor Air Quality—CRI Green Label Plus™	GLP3200, Carpet Category 14X

## WARRANTIES

Lifetime Face Fiber Wear
Lifetime Antistatic
Lifetime Floor Compatibility
Lifetime Color Pattern Permanency
Lifetime Floor Release
Lifetime Moisture Resistance
Lifetime Delamination of Backing
Lifetime Dimensional Stability
Lifetime Tuft Bind
Lifetime Edge Ravel
Lifetime Flammability

## INSTALLATION METHOD



Plank

3<sup>RD</sup> PARTY CERTIFICATES


Design Copyright – Milliken &amp; Company.

This carpet tile product is covered by one or more patents, published applications and/ or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

Customer Service 8621 61455588 | millikencarpet.com

© 2020 Milliken &amp; Company | Made in China