

# Ripple Effect

## Ripple/Breeze



### SPECIFICATION

Construction	Tufted, Textured Loop pile
Face Fiber	100% Milliken-Certified Nylon Type
Tile Size	50 cm x 50 cm (19.7" x 19.7") (Only Breeze) 25cm X 100cm (9.8" X 39.4")
Dye Method	Millitron®
Gauge	1/10
Stitches	14
Standard Backing	PVC-Free WellBAC™ Function Available with TractionBack®
Recyclability	100%
Recycled Content By Total Weight	2.8% (1.1% Post Industrial, 1.7% Post Consumer)
Nominal Total Thickness	0.23" ( 5.8mm)

### PERFORMANCE

Stain Repel / Stain Resist / Soil Release	StainSmart®
Flammability (Radiant Panel ASTM-E-648)	≥ 0.45 (Class I)
Smoke Density (NFPA-258-T or ASTM-E-662)	≤ 450
Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859)	Self-Extinguishing
Lightfastness (AATCC 16E)	≥ 4.0 at 80 Hours
Crocking (AATCC 165)	≥ 4.0 Wet or Dry
Static Electricity (AATCC-134) 20% R.H., 70° F.	≤ 3.5 KV, Permanent Conductive Fiber
Texture Appearance Retention Rating (TARR)	Heavy
Indoor Air Quality—CRI Green Label Plus™	GLP3210, Carpet Category 6Y

### WARRANTIES

- Lifetime Face Fiber Wear
- Lifetime Antistatic
- Lifetime Floor Compatibility
- Lifetime Color Pattern Permanency
- Lifetime Floor Release
- Lifetime Cushion Resiliency
- Lifetime Moisture Resistance
- Lifetime Delamination of Backing
- Lifetime Dimensional Stability
- Lifetime Tuft Bind
- Lifetime Edge Ravel
- Lifetime Flammability
- Lifetime Staining/Soiling (StainSmart®)

### INSTALLATION METHOD



Monolithic



Plank

### 3<sup>RD</sup> PARTY CERTIFICATES



**Design Copyright – Milliken & Company.** This carpet tile product is covered by one or more patents, published applications and/ or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

Customer Service 8621 61455588 | millikencarpet.com  
© 2020 Milliken & Company | Made in China