

Surface Study

Washed/Distressed/Burned



SPECIFICATION	
Construction	Tufted, Textured Loop (with tip shear*)
Face Fiber	ECONYL® Solution-Dyed Nylon
Tile Size	50 cm x 50 cm
Dye Method	Solution Dyed
Gauge	1/12
Stitches	10.4
Standard Backing	PVC-Free WellBAC™ Comfort Available with TractionBack®
Recyclability	100%
Recycled Content By Total Weight	29.8% (19.3% Post Industrial, 10.5% Post Consumer)
Nominal Total Thickness	7.9mm

* For Distressed and Burned pattern

PERFORMANCE		WARRANTIES	
Flammability (Radiant Panel ASTM-E-648)	≥ 0.45 (Class I)	Lifetime Antistatic	
Smoke Density (NFPA-258-T or ASTM-E-662)	≤ 450	Lifetime Floor Compatibility	
Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859)	Self-Extinguishing	Lifetime Color Pattern Permanency	
Lightfastness (AATCC 16E)	≥ 4.0 at 80 Hours	Lifetime Floor Release	
Crocking (AATCC 165)	≥ 4.0 Wet or Dry	Lifetime Face Fiber Wear	
Static Electricity (AATCC-134) 20% R.H., 70° F.	≤ 3.5 KV, Permanent Conductive Fiber	Lifetime Moisture Resistance	
Texture Appearance Retention Rating (TARR)	Severe	Lifetime Delamination of Backing	
Indoor Air Quality—CRI Green Label Plus™	GLP100130, Carpet Category 13X	Lifetime Dimensional Stability	
		Lifetime Tuft Bind	
		Lifetime Edge Ravel	
		Lifetime Flammability	

INSTALLATION METHOD



Monolithic V-Ashlar

3RD PARTY CERTIFICATES


Design Copyright – Milliken & Company.

This carpet tile product is covered by one or more patents, published applications and/ or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

Customer Service 8621 61455588 | millikencarpet.com