

WICKER CONTRACT 2.0

Draftwork / Groundwork



SPECIFICATION

| | |
|----------------------------------|---|
| Construction | Tufted, Textured Loop pile |
| Face Fiber | 100% Milliken-Certified Nylon |
| Tile Size | 1m x 1m (39.4" x 39.4") 50cm x 50cm (19.7" x 19.7") |
| Dye Method | Millitron® |
| Gauge | 1/10 |
| Stitches | 14 |
| Standard Backing | PVC-Free WellBAC™ Comfort Available with TractionBack® |
| Recyclability | 100% |
| Recycled Content By Total Weight | 16.3% (14.4% Post Industrial, 1.9% Post Consumer) |
| Nominal Total Thickness | 0.33" (8.5mm) |

PERFORMANCE

| | |
|---|--------------------------------------|
| Stain Resist / Soil Release | StainSmart® |
| Flammability (Radiant Panel ASTM-E-648) | ≥ 0.45 (Class I) |
| Smoke Density (NFPA-258-T or ASTM-E-662) | ≤ 450 |
| Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859) | Self-Extinguishing |
| Lightfastness (AATCC 16E) | ≥ 4.0 at 80 Hours |
| Crocking (AATCC 165) | ≥ 4.0 Wet or Dry |
| Static Electricity (AATCC-134) 20% R.H., 70°F. | ≤ 3.5 KV, Permanent Conductive Fiber |
| Texture Appearance Retention Rating (TARR) | Severe |
| Indoor Air Quality—CRI Green Label Plus™ | GLP3210, Carpet Category 5Y |

WARRANTIES

- Lifetime Face Fiber Wear
- Lifetime Antistatic
- Lifetime Floor Compatibility
- Lifetime Color Pattern Permanency
- Lifetime Floor Release
- Lifetime Moisture Resistance
- Lifetime Delamination of Backing
- Lifetime Dimensional Stability
- Lifetime Tuft Bind
- Lifetime Edge Ravel
- Lifetime Flammability
- Lifetime Staining/Soiling (StainSmart®)

INSTALLATION METHOD



Monolithic Quarter- turn

3RD PARTY CERTIFICATES


Design Copyright – Milliken & Company. This carpet tile product is covered by one or more patents, published applications and / or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

Customer Service 8621 61455588 |
millikencarpet.com

© 2020 Milliken & Company | Made in China