

URBAN THEORY

FlexForm™ LVT

Milliken

SPECIFICATION

Construction	High Performance FLEXFORM™ LVT
Finish	ProGuard™ Reinforced Polyurethane Coating
Wear Layer Thickness	22 mil (0.55 mm)
Overall Thickness	2.5mm
Edge Profile	Micro Bevel
Tile Sizes	7.25" x 48" (184.15mm x 1219.2mm) 18" x 36" (457mm x 914mm)
Pieces Per Box	16/12
Weight Per Box	16.1kg/22.4kg
Quantity Per Box	3.59 m ² /5.02 m ²

PERFORMANCE


Critical Radiant Flux (ISO 9239-1)	≥4.5kW/m ²
Smoke Rate(ISO 9239-1)	<750%.min
Use Classification (ISO 105-B02)	Class 33 Heavy Commercial
Colour Fastness to Light (ISO 105-B02)	≥6
Slip Resistance (DIN 51130)	R10
Dimensional Stability (ISO 23999)	≤0.25% ; Curl≤2mm
Resistance to Chemicals(ASTM F925)	Pass
Residual Indentation(ISO 24343-1)	≤0.1mm
Castor Chair Resistance (ISO 4918)	Pass
Flexibility (ISO 24344)	Pass

WARRANTIES

15-Year Limited Commercial Wear

Installation

Glue Down Installation



Herringbone Ashlar Vertical Ashlar Random

3RD PARTY CERTIFICATES

Declare.



Milliken LVT is highly durable resilient flooring engineered with the highest quality raw materials to provide unsurpassed performance and enduring aesthetics. Milliken LVT is 100% ortho-phthalate-free. Milliken LVT is manufactured at facilities that are ISO 9001 and ISO 14001 compliant. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Images in this brochure are approximate for color and pattern scale. Please use actual product samples to make your final selections.